

# **TI50A DC Power Supply Battery Charger / Conditioner**



# Features

- Perfect for testing and troubleshooting (avionics, TMDE, electronics, and hydraulics)
- Charges and conditions vehicle batteries when unit is left connected to vehicle
- Ideal for hangars, FOBs, motor pools, and deployments
- · Operates with circuit breakers, therefore eliminating the need to replace blown fuses
- Safe, easy, maintenance-free operation
- 2-year warranty (3-years optional)

### Safe and Easy Operation

- One person can maneuver and operate the unit
- · Safe for flight and travel, non-hazardous
- "Available Power" feature provides instant state of power

#### **Pure Power**

- Operates from 100-260 Vac power 50/60 Hz
- 50 amps continuous @28.5 Vdc (when plugged into ac power)

**Tesla™** Industries, Inc.

www.teslaind.com ♦ www.tesla1.com

Email: tesla1@teslaind.com **Headquarters:** (302) 324-8910

101 Centerpoint Blvd. New Castle, DE 19720 Western Regional Office: (775) 622-8801 9475 Double R Blvd. Suite 2, Reno, NV 89521







# **Technical Specifications, Configurations and Options**

# **Technical Specifications:**

DC Output	50 amps continuous @ 28.5 Vdc (plugged into ac power)
AC Input Power	<ul> <li>Operates from Single Phase 100-260 Vac, 50/60 Hz</li> <li>10 amps @ 120 Vac - 1200 Watts</li> <li>5 amps @ 240 Vac - 1200 Watts</li> </ul>
Vibration	Exceeds MIL-STD-810
Storage Temperature	-65°C to 105°C (-85°F to 221°F)
Operating Temperature w/ AC Power	-40°C to 55°C (-40°F to 131°F)
Dimensions	20.61" L x 5.2" W x 10.56" H 523.49 mm x 132.08 mm x 268.25 mm
Weight	15.85 lbs (7.19 kg)
Warranty	2 years (3 years optional)

### Includes:



A 8ft. DC Aviation Cable **or** a 15ft DC NATO Cable Assembly



A North American AC Line Cord

## **Optional Accessories:**



TI7000-024 TI50A Shipping Case NSN: 6140-01-467-5710



TI7000-046
TI50A Protective Cover



TI7000-184
TI50A Transporting Dolly