

GPU	D.C. Output Specifications				Battery Specifications					A.C. Input Specifications						
	DC Outputs	Output Voltage	Continuous Amps (AC Required)	Watts	Peak Starting Amps	Amp Hrs.	Watt Hours (No AC)	Watt Hours (With AC)	Recharge Time in Minutes	Vac Single Phase	Vac 3Phase	A.C. Input Amps			Watts	Line Frequency Hz
												Single Phase 120 Vac	Single Phase 240 Vac	Three Phase 208 Vac		
TI100 PFC _G	1	28.5	100	2850	-	-	-	-	-	200-260	-	-	20	-	4800	40-600
TI200 PFC _G	1	28.5	200	5700	-	-	-	-	-	200-260	-	-	35	-	8400	40-600
TI500	1	28.5	25	713	750	11.5	256	968	33	95-260	-	10	5	-	1200	50/60/400 _E
TI1000	1	28.5	25	713	1500	23	512	1224	60	95-260	-	10	5	-	1200	50/60
TI1500	1	14.25	20	285	1500	23	512	797	74	95-260	-	5.5	2.75	-	660	50/60
TI1530	1	14.25	20	285	3000	46	1024	1309	143	95-260	-	5.5	2.75	-	660	50/60
TI1550	2	28.5	25	713	50 _B	23	512	1224	60	95-140	-	14.7	-	-	1764	50/60
		14.25	20	285	1500	23	512	797	74	-	-	-	-	-	-	-
TI1560	2	28.5	25	713	1500	23	512	1224	60	95-260	-	14.7	-	-	1764	50/60
		14.25	20	285	1500	23	512	797	74	-	-	-	-	-	-	-
TI2000	1	28.5	25	713	3000	46	1024	1736	115	95-260	-	10	5	-	1200	50/60
TI2500	2	28.5	25	713	3000	46	1024	1736	115	95-260	-	10	5	-	1200	50/60
		28.5	25	713	3000	46	1024	1736	115	-	-	-	-	-	-	-
TI2560	2	28.5	25	713	3000	46	1024	1736	115	95-260	-	14.7	-	-	1764	50/60
		14.25	20	285	3000	46	1024	1309	143	-	-	-	-	-	-	-
TI3000 _A	1	28.5	50	1425	3000	46	1024	2449	60	95-260	-	20	10	-	2400	50/60
TI3500	1	28.5	50	1425	3500	92	2048	3473	115	95-260	-	20	10	-	2400	50/60
TI3560	2	28.5	40	1140	3000	46	1024	2164	74	95-260	-	19.7	-	-	2364	50/60
		14.25	20	285	3000	46	1024	1309	143	-	-	-	-	-	-	-
TI4100	1	28.5	100	2850	1500	23	512	3362	19	200-260	-	-	20 _C	-	4800	50/60
TI4200	1	28.5	200	5700	1500	23	512	6212	12	-	200-260	-	-	20 _C	7205	50/60
TI4200 PFC _G	1	28.5	200	5700	1500	23	512	6212	12	200-260	-	-	35 _C	-	8400	40-600
TI4400	1	28.5	400	11400	1500	23	512	11912	8	-	200-260	-	-	40 _D	14411	50/60
TI5100	1	28.5	100	2850	3000	46	1024	3874	33	200-260	-	-	20 _C	-		50/60
TI5200	1	28.5	200	5700	3000	46	1024	6724	19	-	200-260	-	-	20 _C	7205	50/60
TI5200 PFC _G	1	28.5	200	5700	3000	46	1024	6724	19	200-260	-	-	35 _C	-	8400	40-600
TI5400 _A	1	28.5	400	11400	3000	46	1024	12424	12	-	200-260	-	-	40 _D	14411	50/60/400 _F

- Notes:**
- A: Additional GPU configurations available.
 - B: Circuit breaker limited.
 - C: Requires 30 amp service contact Tesla ind. for receptacle information.
 - D: Requires 60 amp service contact Tesla ind. for receptacle information.
 - E: Requires appropriate line cord for 120 Vac, 240 Vac and 400 Hz operations.
 - F: 400 Hz is available on GHMD and UAV ACDC models only.
 - G: Features 0.999 Active Power Factor Correction.