



Power Anytime, Anywhere

TI5400 GPU-24

NSN: 6130-01-452-2807

CL IX



Pure Power - No Spikes or Surges

- 24 VDC for engine starting
- 400 amps of continuous 28.5 VDC power (plugged into AC power) for testing and troubleshooting avionics and weapons systems
- Technology upgrades available

Perfect Aircraft Ground Power/Starting Solution

- 3000 peak starting amps
- Eliminates hot starts
- Ideal power for maintenance hangars, FARPs, and deployment

Safe and Easy Operation

- One person can maneuver and operate the unit
- Non-hazardous, dry-cell technology
- "Push to Test" feature provides instant state of charge

Maintenance-free Performance

- Operates from 208 - 240 AC power, 3-phase
- Simply plug into AC power when not in use
- 5 to 7-year service life with a 2-year warranty (3-years optional)

Specifications

- **Size:** 50" L x 24.5" W x 16" H (1270 mm x 622.3 mm x 406.4 mm)
- **Weight:** 251 lbs (113.85 kg)

Input Requirements

- 60Hz - runs/charges from 3-phase 208-240 VAC power 60 amps

Tesla™ Industries, Inc.

www.teslaind.com

Email: tesla1@teslaind.com

Headquarters: (302) 324-8910

109 Centerpoint Blvd. New Castle, DE 19720 USA

Western Regional Office: (775) 622-8801

9475 Double R Blvd. Suite 2, Reno, NV 89521 USA



5/13/09